


Avery Dennison Y5966 is a pre-combined diaper tape system, incorporating hook elements and a Y-bond between fastening and release tape.

- Nonwoven-like fastening tape increasing the softness of the closure system
- Combination of hook element and adhesive providing high peel and shear performance on nonwoven backsheets
- Excellent adhesion of release tape to a wide variety of polyethylene and polypropylene nonwoven substrates
- Y-bond providing strongest possible bond with diaper chassis
- Long release tape enhancing tape conversion on diaper line

CONSTRUCTION:

1. White soft nonwoven fastening tape, 62 mm
2. White fingerlift strip, 7 mm
3. Superhook elements, 12 mm
4. Clear PP release tape (incl. Y-bond), 44 mm
5. Folding position, 19 mm
6. Adhesive next to hook – fingerlift side, 13 mm
7. Adhesive next to hook – hinge side, 5 mm



STANDARD FORMAT:

- Roll width: 62 mm
- Roll length: 3600 linear meter
- Inside diameter of the core: 76 mm
- Outside diameter of the roll: 620 mm

PACKAGING:

- Standard export packaging
- Pallet size is 1200 x 1000 x 1170 mm (height)
- Number of rolls per pallet, 4

Physical Properties	Typical Values	Test Methods
PRECOMBINED TAPE		
Roll unwind release	Low	
FASTENING TAPE		
90° peel Hooks/Avery Loops (peak)	300 N/m	T04/612
FASTENING TAPE – PERMANENT PART		
90° peel on PE film	140 N/m	T04/100
RELEASE TAPE		
90° peel on PE film	200 N/m	T04/100

Note: The listed values are typical only and not intended to serve as product specifications. Test procedures conform PSTC – ASTM – ISO.

STORAGE AND SHELF LIFE:

The shelf life of the product is one year when stored in original packaging at 15°C-30°C, 30-70% relative humidity and out of direct sunlight.

IMPORTANT:

Information on the above characteristics is based upon tests we believe to be reliable. The values given are typical values that vary according to application conditions. The values are intended only as a source of information and are given without guarantee and do not constitute a warranty. Purchasers should independently determine prior to use the suitability of this material for their specific purposes. All Avery Dennison materials described herein are sold subject to Avery Dennison Conditions of Sales, a copy of which is available upon request.

Please refer to **Tapes.AveryDennison.com** for complete terms and conditions, including warranty terms, relating to this product. You should periodically review the site as terms and conditions are subject to change without notice.

© 2018 Avery Dennison Corporation. All rights reserved. Avery Dennison® is a registered trademark of Avery Dennison Corporation. All other Avery Dennison brands, product names, antenna designs and codes or service programs are trademarks of Avery Dennison Corporation.

Asia Pacific

Kunshan, China,
NO. 618 Nanhe Road
Kunshan Economic &
Technological Zone
China, 215335
Phone: +86 512 57155001
Fax: +86 512 57155059

Europe

Tieblokkenlaan 1
B-2300 Turnhout
Belgium
Phone: +32 (0)14 40 48 11
Fax: +32 (0)14 40 48 55

North America

250 Chester Street
Painesville, Ohio
44077 USA
Phone: +1 866-462-8379
Fax: +1 888-358-4469